



11th Southern African Water Loss Summit

Supported by:
The International Water Association
Water Loss Specialist Group



LIVE 20 & 21 August 2024
2008 ONLINE EVENT



IN-SITU VERIFICATION TO REDUCE APPARENT LOSSES

Presented by
Keabetswe Lekalakala

Supporting organisations:



OVERVIEW

IN-SITU METER VERIFICATION

- WHAT?
- WHY?
- WHERE?
- HOW?
- RESULTS AND FINDINGS
- CONCLUSION



What is In-situ Meter Verification

- In-situ verification means that a unit or parameter can be measured in its position or onsite to determine if the performance of the meter is still in line with its original factory-calibrated values.
- Whether a meter is installed in a water or wastewater application, the accurate measurement of flow is a critically important requirement.
- An In-situ verification check does not calibrate a flowmeter but rather verifies the meter accuracy.
- This method provides means of checking flowmeter performance without the disruption and added expenditure associated with removing the meter and calibrating it in a laboratory.




Why do we conduct In-situ verification

- All instrumentation, whether a flowmeter or another type of instrumentation, loses its accuracy over time due to wear and tear and other factors stated below:
 - ✓ Meter Age
 - ✓ Incorrect installation
 - ✓ Incorrect pipe sizing
 - ✓ Inappropriate meter type
 - ✓ Low flow rates
 - ✓ Environmental impacts
- To correct this loss in accuracy, instrumentation needs to be regularly tested or verified, and re-calibrated if necessary.
- Regulation 131 of 2017 of the Department of Water and Sanitation requires that the accuracy of a water measuring device be "verified at least once every five years or for such period as required by the manufacturer"
- Common methods of verifying a flowmeter are:
 - Using a master meter (Ultrasonic Clamp-on Meter)
 - Volumetric calibration.



How In-situ verification is conducted - Ultrasonic clamp-on meter

- A non-invasive device used to measure full pipe flow in closed conduits.
- These meters are unique in their ability to measure flow with little or no modification to existing pipe configuration



Why do we conduct In-situ verification

- Using an ultrasonic meter to verify and re-calibrate your flowmeter is a valid method, but only if the ultrasonic meter itself has been recently calibrated, or verified and re-calibrated, through a process that can be traced back to some national or international standard.
- The South African National Accreditation System (SANAS) is mandated through the Accreditation for Conformity Assessment, Calibration and Good Laboratory Practice Act (Act 19 of 2006) to accredit calibration laboratories.
- Practical limitations of the meters performance and the limitations of the hydraulic system in which they are installed can restrict the flow range over which they can be tested/calibrated.



Metrological Data – Xylem Water Meters


METROLOGICAL DATA ACC. TO MANUFACTURERS VALUES

Size	DN	40	50	65	80	100
Q_{max} Max. Peak Flow	m³/h	60	90	120	200	300
Q_{max} Continuous Flow	m³/h	40	50	70	120	230
Q_{min} Transitional Flowrate horizontal	m³/h	0.32	0.4	0.63	0.51	0.81
Q_{min} Minimum Flow horizontal	m³/h	0.2	0.15	0.2	0.2	0.3
Q_{min} Transitional Flowrate vertical	m³/h	0.4	0.51	0.81	0.8	1.28
Q_{min} Minimum Flow vertical	m³/h	0.25	0.28	0.4	0.5	0.5
Starting Flow	m³/h	0.05	0.05	0.07	0.1	0.11

Size	DN	125	150	200	250	300
Q_{max} Max. Peak Flow	m³/h	350	600	1200	1600	2000
Q_{max} Continuous Flow	m³/h	250	450	800	1250	1400
Q_{min} Transitional Flowrate horizontal	m³/h	1.02	1.6	4.0	6.3	16.0
Q_{min} Minimum Flow horizontal	m³/h	0.5	0.8	2.0	3.5	9.0
Q_{min} Transitional Flowrate vertical	m³/h	1.6	3.2	4.0	10.1	25.4
Q_{min} Minimum Flow vertical	m³/h	1	1.6	2.5	6.3	15.9
Starting Flow	m³/h	0.15	0.3	1.5	3	6



Meter Design Curve



Measurement principle and systems

- The measurement system consists of a transmitter, the ultrasonic transducers with the transducer cables and the pipe on which the measurement is conducted.
- The ultrasonic transducers are mounted on the outside of the pipe.
- Ultrasonic signals are sent through the medium and received by the transducers.
- The transmitter controls the measuring cycle, eliminates the disturbance signals and analyzes the useful signals. The measured values can be displayed, used for calculations and transmitted
- The transmission speed of an ultrasonic signal depends on the flow velocity of the carrier medium (water).



The Transit - Time Difference Principle (Δt)

- Sound Speed (c) – Calculated from the measured time difference
 - Flow velocity (v) – Calculated based on the measured transit-time difference (Δt).
 - Volumetric flow rate (V) – Calculated by,
 $V = (\text{Pipe x-sectional Area})(\text{flow velocity})$.
 - Mass flow rate (m) – Calculated by,
 $m = V \times (\text{operating Density of the medium})$.
- Note : Knowledge of quantities and their correct standard international units is required.





Methodologies to In-situ Verification Installations

- Ultrasonic Meter should be calibration before utilising and ensure certificate is valid.
 - SANAS Accreditation
- Pipeline needs to be inspected
- Preparation of the pipe.
 - Cleaning and ensuring pipe
 - Removing any lining in position of transducers.
- Identify possible transducer positioning.



Preparation for Installation



In-situ Verification on Electromagnetic Flow Meters



14

In-situ Verification on Mechanical Flow Meters



15


In-situ verification challenges/limitations

- Illegible meter dials.
- Damaged meter dials.
- Meter reading error where readings are captured manually.
- Incorrect scale factor considerations
 - 1 x m3, 10m3, x 100 m3

16


Low Flow Rates

BEFORE



Low Flow Rates

AFTER



17

In-situ Meter Verification Errors

- All water meters must also be verified to prove that the measurement of water used is accurate to within +/- 5% error margin, this however is depended on various factors such as meter age, flow rates, environmental impacts, meter size.
- To achieve this level of accuracy, the correct verification method must be selected for each installation.

18

In-situ verification measurement errors



- These can be caused by non-uniform pipe thickness, differing water temperature, air bubbles, oval pipe.
- Signal between transducers and pipe work, low signal strength caused by pipe makeup, pipe build up rust.
- To do this, record site details will need to be kept on dimensional characteristics of the pipe, set-up parameters, diagnostics parameters and relevant observations.
- This data can then be used to verify or confirm measurements made on site and reduce the potential for human error.

20

Percentage error margin Calculations



$$\text{Percentage Error} = \left[\frac{\Delta \text{Meter Readings}}{\Delta \text{UDM Readings}} - 1 \right] \times 100\%$$

- Meter Consumption = Δ Meter Readings
- UDM Consumption = Δ UDM Meter Readings

21

Relative Error - Calculations



- The ultrasonic clamp-on meter is considered the true measurement (known).
- Bulk Meter is the observed measurement.

Verification consideration (Ultrasonic Meter)

- Start reading & end reading remains the same. Verification is considered as: **No Flow**

Error margin within -5% and +5%

Error % = -100

In-situ verification results



Consumer Name & Address	Meter Serial No	Start Date	Completion Date	Start Reading (m³)		Completion Reading (m³)		Consumption (m³)		Consumption Difference (m³)	Error in %
				Ultrasonic Meter	Consumer Meter	Ultrasonic Meter	Consumer Meter	Ultrasonic Meter	Consumer Meter		
Verification 1	SN 2984471	2024/04/10	2024/04/11	30841.952	2012.258	38851.185	2039.629	11.833	11.873	0.040	0.34%
Verification 2	SN 8026311	2024/04/10	2024/04/11	1132.490		28029.219		24896.729	0.000	-24896.729	-100.00%
Verification 3	SN 8728763	2024/04/10	2024/04/11	48957.332	695405.290	49046.518	610373.220	5208.178	4917.960	-298.218	-5.73%
Verification 4	SN 34517431	2024/04/10	2024/04/11	785371.880	5253481.360	792371.236	5270878.080	18966.376	17387.720	-368.344	-1.94%
Verification 5	SN 56381900	2024/04/11	2024/04/12	26045.41	1107943.76	34816.88	1115444.240	8770.469	7500.480	-1269.989	-14.48%
Verification 6	SN 05271734	2024/04/11	2024/04/12	782377.271		785942.471		3165.200	0.000	-3165.200	-100.00%
Verification 7	SN 13273482	2024/04/11	2024/04/12	499048.307	121077.180	494548.838	121498.240	388.531	391.890	2.549	0.66%
Verification 8	SN 21384679	2024/04/11	2024/04/12	36954.145	588317.530	38710.852	570960.500	3658.807	2542.860	-114.337	-3.12%
Verification 9	SN 4648299	2024/04/18	2024/04/17	550286.545	1228784.850	509350.807	1234741.320	9054.06	8946.67	-107.39	-1.19%
Verification 10	SN 8321945	2024/04/18	2024/04/17	42585.848	148105.490	43027.383	148190.050	958.55	854.55	-104.00	-10.85%
Verification 11	SN 63481210	2024/04/18	2024/04/17	789887.087	698854.130	792737.275	700852.880	3848.71	3998.55	149.84	3.90%
Verification 12	SN 3830016	2024/04/18	2024/04/17	34876.325	32091.000	35145.867	32348.290	286.84	254.29	-31.55	-11.35%

22

METER ACCURACY ERROR



- Meter Age
- Incorrect installation
- Incorrect pipe sizing
- Inappropriate meter type
- Low flow rates
- Environmental impacts

24

In-situ meter verification installations



25


Meter inaccuracies due to broken or incorrect customer and water meters.



Bulk Meter Findings



Low Flow Rates




Low Flow Rates

Meter Size	100
Make	Sensus Metstream
Pipe O/D	114.9
Pipe Thickness	5.8
Lining Material & Thickness	No Lining
Transducer Spacing	34.7
Date Installed	2022/04/28 10:43:00 AM
Date Removed	2022/04/28 10:53:00 AM
Duration Of Operation	1 days 0 hours 12 minutes
Path Method & Traverse	3 Diagonal
Sensors	Standard
Meter Reading Start (m³)	1 642.5200
Meter Reading End (m³)	1 665.2000
Meter Consumption (m³)	22.6800
Ultrasonic Start (m³)	124 818.5000
Ultrasonic End (m³)	124 832.7240
Ultrasonic Consumption (m³)	17.2240
Difference Between Meter & Ultrasonic (m³)	5.4560
Error %	31.63%

In-Verification Flow Impacts


Meter Size	100
Make	Sensus
Pipe O/D	114.9
Pipe Thickness	5.8
Lining Material & Thickness	No Lining
Transducer Spacing	34.7
Date Installed	2022/04/28 10:43:00 AM
Date Removed	2022/04/28 10:53:00 AM
Duration Of Operation	1 days 0 hours 12 minutes
Path Method & Traverse	3 Diagonal
Sensors	Standard
Meter Reading Start (m³)	1 642.5200
Meter Reading End (m³)	1 665.2000
Meter Consumption (m³)	22.6800
Ultrasonic Start (m³)	124 818.5000
Ultrasonic End (m³)	124 832.7240
Ultrasonic Consumption (m³)	17.2240
Difference Between Meter & Ultrasonic (m³)	5.4560
Error %	31.63%



Low Flow Rates

BEFORE

AFTER



Meter Conditions – Vandalized meters, broken dials



Conclusion

- In-situ verification plays a pivotal role in ensuring the accuracy of water meters, which directly impacts the reliability of billing systems.
- Regular field checks and calibration of meters enable utilities to identify and address potential issues before they escalate.
- In-situ verification provides valuable data that can be used to identify patterns and trends in meter performance across the distribution network.
- This data-driven approach allows utilities to make informed decisions about meter management, optimize maintenance schedules, and invest in upgrades that further reduce NRW.
- Investing in in-situ verification processes can lead to substantial long-term savings by reducing the need for extensive system overhauls or costly corrections of billing errors.

31



If you can't measure it. You can't manage it

32

THANK YOU

33